D-mig 6 LAB


IT EN

- MIG/MAG
- TRADITIONAL 3PH

Carpenteria pesante
Heavy carpentry

Tubazioni
Pipeline







Supporto torcia
Torch holder

La proposta DECA per la carpenteria pesante. Solidi generatori tradizionali progettati per sostenere cicli intensivi di lavoro.

- Il controllo MIG Synergic facilita il lavoro del saldatore gestendo in sinergia con le altre impostazioni della saldatrice, la velocità del filo, la rampa iniziale ed il **Burn back**. Il saldatore deve soltanto attivare uno dei programmi preimpostati.
- Robuste ed affidabili.

The DECA proposal for heavy carpentry. Solid traditional generators designed to support intensive work cycles.

- The Synergic MIG control facilitates the welding machine operator's work as it manages wire speed, soft start and **Burn back** in a synergic way with the rest of the machine settings. The welding machine operator must simply activate one of the pre-set programs.
- Sturdy and durable.

Simple Weld

Synergic Digital Control





D-mig 7

Traino 4 rulli ingranati
4 geared rolls feeder

D.30mm

deca

MADE IN SAN MARINO		D-mig 635 T LAB	D-mig 650 T LAB	D-mig 635 TD LAB	D-mig 650 TD LAB
Tensione di rete: 50/60Hz Input voltage: 50/60Hz		**3 ~ 230 / 400V**			
Potenza assorbita: 60% / Max Absorbed power: 60% / Max		5,5 / 8,5 kW	10 / 16 kW	5,5 / 8,5 kW	10 / 16 kW
Fusibile - Fuse		25/16A	50/32A	25/16A	50/32A
Rendimento - Efficiency		< 80%	< 80%	< 80%	< 80%
Campo di regolazione Welding current		**25 - 350A**	**30 - 500A**	**25 - 350A**	**30 - 500A**
Posizioni di saldatura - Welding positions		10	21	10	21
Servizio - Duty cycle (40°C EN 60974-1)		270A - 32%	410A - 33%	270A - 32%	410A - 33%
		200A - 60%	310A - 60%	200A - 60%	310A - 60%
Tensione a vuoto - Open circuit voltage		17 - 41V	17 - 49V	17 - 41V	17 - 49V
Filo ø mm Wires ø mm	Acciaio - Steel	0,8 - 1,0 - 1,2 - 1,6		0,8 - 1,0 - 1,2 - 1,6	
	Inox - Stainless steel	0,8 - 1,0 - 1,2 - 1,6		0,8 - 1,0 - 1,2 - 1,6	
	Al.Mg 5 - Al.Si 5	1,0 - 1,2 - 1,6		1,0 - 1,2 - 1,6	
	Animato Flux cored FCAW-G	1,2 – 1,6		1,2 - 1,6 (manual)	
	Bobina Ø mm Wire spool Ø mm	200 - 300			
Trainafilo - Wire feeder		4 ingranati- 4 geared rolls (30 Ø mm)			
Amperometro / Voltmetro Ammeter / Voltmeter		–		•	
Caricamento filo - Wire load		–		•	
Modo pulsante torcia - Torch trigger mode		2T / 4T / Spot		2T / 4T / Spot / Stitch	
Saldatura sinergica Synergic welding		–		•	
Accostamento filo - Approach speed		Regolabile - Adjustable			
Regolazione fine velocità filo Fine speed regulation		Regolabile - Adjustable			
Burn Back		Regolabile - Adjustable			
Connessioni in uscita - Output connections		Euro / DX 70 mmq			
Peso - Weight ≃		95 kg	122 kg	95 kg	95 kg
Dimensioni - Dimensions		870 x 540 x 1020 mm			
Codice - Code		**262200**	**263799**	**262600**	**263499**

D-mig 635T, 635TD: accessori in dotazione - Supplied accessories:


DE M25A: 230A - 3m (Ugello / Tip 1,0mm)


Fe 0,6 / 0,8 / 1,0
1,2 / 1,6 mm


3,0m 35mmq


Gas 1,5m

D-mig 650T, 650TD: accessori in dotazione - Supplied accessories:


Fe 0,6 / 0,8 / 1,0
1,2 / 1,6 mm


3,0m 35mmq


Gas 1,5m