ART.150

Polishing machine for bent pipes and straight pipes



Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com

General technical info

Power supply	400 | 50 | 3	Volt|Hz|Phase
Disc motor power	1,8 (2,5)	kW (hp)
Abrasive belt motor power	3,3 - 2,6 (4,5 - 3,5)	kW (hp)
Motor speed	2800 - 1400	rpm
Peripheral speed	25 - 10	m/sec
Abrasive belt dimension (wide x length)	(2x) 60 x 900	mm
Overall dimension (Width x Depth x Height)	750 x 910 x H. 1550	mm
Acoustic emission	80	dB
Weight standard machine	360	kg
Dust extraction connection	ø 80	mm
Stations	1	No.
Workpiece diameter allowed	ø 5 ÷ ø 120	mm
Minimum radius bend pipe	R. 150	mm

Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments



Pedal tape opening command
Essential accessory supplied.By operating the pedal it allows the opening of the abrasive belts, facilitating the insertion of the piece and avoiding the breaking of the abrasive belts.



Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Copyright © Aceti Macchine s.n.c. | All rights reserved

Optional Equipments



cod. **ASP.01-HP2**: **Dust extractor by cyclone system**
Wheeled dust extractor with cyclone system. It is built entirely of steel and has no dust filter bag. The suction takes place by means of the centrifugal force generated by the cyclone which conveys the dust into the underlying steel drawer that collects and holds it. In the case of dry machining it is necessary to connect the machine to a strong vacuum cleaner such as this which keeps the conveyor belt clean from the emery.

>>> Product Datasheet <<<

Seq. 30 - Rel.
Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Copyright © Aceti Macchine s.n.c. | All rights reserved