
ART.15

Electric portable bevelling machine



Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com

ART. 15	SMUSSATRICE PORTATILE ELETTRICA V.48 PORTABLE ELECTRIC CHAMFERING MAC. CHANFREINEUSE PORTATIVE ELECTRIQUE KANTENFRÄSMASCHINE TRAGBAR V.48							
 Volt 400→Volt 48 kW 0,75						 kg	
hp	Rpm	m/s	dB	E	F	G	kg
1	2800	12	68	250	400	260	16
 ISO SPUN 12.03.08							
Ø mm	Z		P	R	T	Sm	J°
80	20		250	80	80	0÷20	15°÷45°

Seq. 02991 - Rel. 280721
Copyright © Aceti Macchine s.n.c. | All rights reserved

General technical info

Power supply	Input 400 | 50 | 3 Output 48 | 50 | 3	Volt|Hz|Phase
Motor power	0,75 (1)	kW (hp)
Motor speed	2800	rpm
Acoustic emission	68	dB
Overall dimension (Width x Depth x Height)	400 x 250 x H. 260	mm
Weight standard machine	16	kg

• Chamfer - bevel unit

Bevel dimension (diagonal)	0 ÷ 20	mm
Bevel angle	15 ÷ 45	°
Milling cutter diameter	ø 80	mm
Quantity of widia insert milling cutter	20	No.
Widia insert type/code	SPUN 12 03 08	ISO
Support table dimension	80 x 250	mm
Peripheral speed	12	m/sec

Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments



Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Technical general information

- Hardened, case hardened, ground and grooved guides for prolonged resistance to friction.

- Axial displacement of the guides for full use of the insert surface.

- Tilting beveling guide with graduated indicator for bevels from 15 ° to 45 °.

- Bevel size adjustment handwheel.

- Cutter body complete with 20 widia inserts.

Seq. 02991 - Rel. 280721
Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Copyright © Aceti Macchine s.n.c. | All rights reserved