

ART.61

Bevelling machine



Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com

ART. 61	SMUSSATRICE DA BANCO CHAMFERING MACHINE FOR DESK CHANFREINEUSE DE BANC KANTENFRÄSMASCHINE FÜR WERKBANK							
 Volt 400 kW 1,1								
hp	Rpm	m/s	dB	E	F	G	G1	kg
1,5	2800	12	68	400	500	500	245	32
 ISO SPUN 12.03.08								
Ø mm	Z		P	R	T	Sm	J°	
80	10		500	80	100	0÷6	15°÷45°	

Seq. 02800 - Rel. 270721
Copyright © Aceti Macchine s.n.c. | All rights reserved

General technical info

Power supply	400 | 50 | 3	Volt|Hz|Phase
Motor power	1,1 (1,5)	kW (hp)
Motor speed	2800	rpm
Acoustic emission	68	dB
Overall dimension (Width x Depth x Height)	500 x 400 x H. 500	mm
Weight standard machine	32	kg

• Chamfer - bevel unit

Bevel dimension (diagonal)	0 ÷ 6	mm
Bevel angle	15 ÷ 45	°
Milling cutter diameter	ø 80	mm
Quantity of widia insert milling cutter	10	No.
Widia insert type/code	SPUN 12 03 08	ISO
Support table dimension	100 x 500	mm
Peripheral speed	12	m/sec

Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments



Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base
Stable bench structure with anti-vibration rubbers at the base.

Electrical panel
Electric controls with emergency stop and anti-reset function for accidental starting and electronic overload protection.

Hardened guide coating
Rectified and grooved guides with hardening treatment for a prolonged friction resistance.

Axial movement
Axial displacement for full use of the cutting surface of the inserts.

Seq. 02800 - Rel. 270721
Copyright © Aceti Macchine s.n.c. | All rights reserved

Variable chamfer angle
Chamfering guide with index for bevels from 15 ° to 45 °.

Handwheel
Handwheel for chamfer dimension adjustment.

Miller body
Milleler body complete with 10 tungsten carbide inserts.

Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Seq. 02800 - Rel. 270721
Copyright © Aceti Macchine s.n.c. | All rights reserved