
ART.22

Belt grinding machine



Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com

ART. 22	LEVIGATRICE A NASTRO DA BANCO BELT GRINDING MACHINE FOR DESK TANK DE BANC BANDSCHLEIFMASCHINE FÜR WERKBANK							
 Volt 400 kW 1,1								kg
hp	Rpm	m/s	dB	E	F	G	G1	kg
1,5	2800	15	70	550	450	600	150	28
				OPTIONALS				
								
A	B	C	D	Ø	BAS.01		ASP.04	
1000	100	290	100	100	kg 40		kg 45	

Seq. 01000 - Rel. 250521
Copyright © Aceti Macchine s.n.c. | All rights reserved

General technical info

Power supply	400 | 50 | 3	Volt|Hz|Phase
Motor power	1,1 (1,5)	kW (hp)
Motor speed	2800	rpm
Acoustic emission	70	dB
Overall dimension (Width x Depth x Height)	450 x 550 x H. 600	mm
Weight standard machine	28	kg

• Belt grinder unit

Abrasive belt dimension (wide x length)	100 x 1000	mm
Peripheral speed	15	m/sec
Dimension of working plane (behind abrasive belt)	100 x 290	mm
Driving wheel dimension	ø 100	mm
Orientable belt grinding arm	0 ÷ 90	°

Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments



Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base
Stable bench structure with anti-vibration rubbers at the base.

Electrical panel
Electric controls with emergency stop and anti-reset function for accidental starting and electronic overload protection.

Orientable arm sander
Arm sander adjustable from 0 ° to 90 ° and intermediate positions.

Type of work
Three types of processing, in plan with support, on tyred wheel, on tyred wheel with support.

Seq. 01000 - Rel. 250521
Copyright © Aceti Macchine s.n.c. | All rights reserved

Work surface
Behind the abrasive tape has a durable floor in abutment replaceable steel over time.

Rubberized grooved wheel
Rubberized, grooved and balanced drive wheel for better drag of the abrasive belt.

Abrasive belt
Abrasive belt mounted on the machine ready for use.

Belt grinder cover
Carter sander with predisposition connection system.

Copyright © Aceti Macchine s.n.c. | All rights reserved


Optional Equipments




cod. **BAS.02**: **MACHINE STAND**
Strong stand with anti-vibration rubber and inside a useful space for tools. Dimensions 300X200 X H.750 - KG 25



cod. **BAS.02+IA-1**: **MACHINE STAND WITH DUST EXTRACTION ONE CONNECTION**
STAND WITH DUST EXTRACTOR kit with one suction mouth: complete of dust filter bag in flexible aluminum pipe and hose clamps. The extractor is wired to the electrical panel.TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m3 / h- Max total pressure: 85 mm H2O



cod. **M1V-MF**: **SINGLE PHASE MOTOR ONE SPEED**
Single phase motor one speed Rpm 2800 230 volts - 50 Hz - 1 phase



cod. **M2V-MF**: **TWO SPEEDS SINGLE PHASE MOTOR**
Two speeds single phase motorRpm 1400/2800 230 volts - 50 Hz - 1 phase



cod. **M2V-TA**: **TWO SPEEDS MOTOR**
Two speeds three-phase motor Rpm 1400/2800, recommended for use with stainless steel and aluminum.400 volts - 50 Hz - 3 phase



cod. **INV-MF**: **VARIABLE SPEEDS SINGLE PHASE**
Single-phase inverter for electronic regulation of motor revolutions from 300 ÷ 3000 Rpm.The inverter is supplied inside box for the dust protection, which can be controlled with potentiometer.Motor with maximum power 1,1 kW.

Seq. 01000 - Rel. 250521
Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Copyright © Aceti Macchine s.n.c. | All rights reserved