
ART.73N

Belt grinding machine



Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com



hp	Rpm	m/s	E	F	G	G1	dB	kg	A	B	Ø	D	M	N	P	T	J°	ASP.01
4	1400 2800	10 20	1050	550	1200	910	70	225	1750	200	135	200	565	300	565	300	-45°/+45°	kW 1.5

Seq. 07000 - Rel. 230621
Copyright © Aceti Macchine s.n.c. | All rights reserved

General technical info

Power supply	400 | 50 | 3	Volt|Hz|Phase
Motor power	3,3 - 2,6 (4,5 - 3,5)	kW (hp)
Motor speed	2800 - 1400	rpm
Acoustic emission	70	dB
Overall dimension (Width x Depth x Height)	1050 x 550 x H. 1200	mm
Weight standard machine	225	kg

• Belt grinder unit

Abrasive belt dimension (wide x length)	200 x 1750	mm
Peripheral speed	20 - 10	m/sec
Dimension of working plane (behind abrasive belt)	565 x 300	mm
Driving wheel dimension	ø 135	mm
Orientable belt grinding arm	0	°
Support table dimension	565 x 300	mm
Support table revolution	- 45 ÷ + 45	°

Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments



Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base
Strong base with anti-vibration rubbers at the base and a useful shelf for tools inside.

Electrical panel
Low voltage electric controls with padlock device integrated in the main electric switch.

Electronic brake card
Emergency stop with electronic motor braking with safety anti-reset function.

Motor
Motor 2 speeds

Seq. 07000 - Rel. 230621
Copyright © Aceti Macchine s.n.c. | All rights reserved

Type of work
Two types of work:- Plan for special support of the surface plate processing:tiltable with graduated indicator -45 ° to + 45 ° and intermediate positions height adjustable by means of handwheel for the full utilization of the cutting surface of the abrasive tape.- special support plan for working on rubber wheel:tiltable with graduated indicator -45 ° to + 45 ° and intermediate positions adjustable height for the full utilization of the cutting surface of the abrasive tape.

Work surface
Behind the abrasive tape has a durable floor in abutment replaceable steel over time.

Rubberized grooved wheel
Rubberized, grooved and balanced drive wheel for better drag of the abrasive belt.

Abrasive belt
Abrasive belt mounted on the machine ready for use.

Belt grinder cover
Carter sander with predisposition connection system.

Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Seq. 07000 - Rel. 230621
Copyright © Aceti Macchine s.n.c. | All rights reserved