ART.131

Belt grinding machine



Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com

General technical info

Power supply	400 | 50 | 3	Volt|Hz|Phase
Motor power	0,85 - 0,65 (1,15 - 0,9)	kW (hp)
Motor speed	2800 - 1400	rpm
Acoustic emission	70	dB
Overall dimension (Width x Depth x Height)	600 x 1100 x H. 1400	mm
Weight standard machine	110	kg

• Belt grinder unit

Abrasive belt dimension (wide x length)	50 x 2250	mm
Peripheral speed	36 - 18	m/sec
Driving wheel dimension	ø 250	mm
Orientable belt grinding arm	0	°

Seq. 05202 - Rel.
Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments



Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Technical general information

- Back plate behind the steel abrasive belt.

- Rubberized drive wheel and rubberized contact wheel, splined and balanced.

- Abrasive belt mounted on the machine ready to use.

- Transparent spark arrestor protection with friction joint.

- Carter sander with predisposition for connection of suction system Ø60mm.

Copyright © Aceti Macchine s.n.c. | All rights reserved

Optional Equipments



cod. **IA-1**: **DUST EXTRACTOR - ONE CONNECTION**
DUST EXTRACTOR kit with one suction mouth: complete of dust filter bag in flexible aluminum pipe and hose clamps. The extractor is mounted inside the base and wired to the electrical panel.TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m3 / h- Max total pressure: 85 mm H2O

Seq. 05202 - Rel.
Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Copyright © Aceti Macchine s.n.c. | All rights reserved