

ART.33

Belt grinding machine



Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com

ART. 33	LEVIGATRICE ORIENTABILE A NASTRO ORIENTABLE BELT GRINDING MACHINE BACKSTAND SCHWENKBARE BANDSCHLEIFMASCHINE							
 Volt 400 kW 3,7								 kg
hp	Rpm	m/s	dB	E	F	G	G1	kg
5	1400 2800	18 36	75	1100	700	1150	830	150
						 OPTIONAL		
A	B	C	D	Ø	IA-2			
2000	75	470	100	250	kW 0,55			

Seq. 02003 - Rel. 260821
Copyright © Aceti Macchine s.n.c. | All rights reserved

General technical info

Power supply	400 | 50 | 3	Volt|Hz|Phase
Motor power	3,7 - 2,2 (5 - 3)	kW (hp)
Motor speed	2800 - 1400	rpm
Acoustic emission	75	dB
Overall dimension (Width x Depth x Height)	1100 x 700 x H. 1150	mm
Weight standard machine	150	kg

• Belt grinder unit - wheel processing

Abrasive belt dimension (wide x length)	75 x 2000	mm
Peripheral speed	36 - 18	m/sec
Dimension of working plane (behind abrasive belt)	100 x 470	mm
Driving wheel dimension	ø 250	mm
Orientable belt grinding arm	- 30 ÷ + 30	°

Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments



Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base
Strong base with anti-vibration rubbers at the base and a useful shelf for tools inside.

Electrical panel
Low voltage electric controls with padlock device integrated in the main electric switch.

Electronic brake card
Emergency stop with electronic motor braking with safety anti-reset function.

Motor
Motor 2 speeds

Seq. 02003 - Rel. 260821
Copyright © Aceti Macchine s.n.c. | All rights reserved

Belt grinder head
The belt grinder head is adjustable from -30 ° to + 30 ° and intermediate positions.

Support plane
Orientable support surface for working in support near the front contact wheel.

Front contact wheel
Front contact wheel rubberized grooved and balanced

Rubberized drive wheel
Rubberized and balanced drive wheel for better drag of the abrasive belt.

Work surface
Behind the abrasive tape has a durable floor in abutment replaceable steel over time.

Abrasive belt
Abrasive belt mounted on the machine ready for use.

Copyright © Aceti Macchine s.n.c. | All rights reserved

Dust collection
Dust collection drawer placed under the contact wheel.

Belt grinder cover
Carter sander with predisposition connection system.

Anti-spark repair
Transparent protection arrester with friction joint.

Seq. 02003 - Rel. 260821
Copyright © Aceti Macchine s.n.c. | All rights reserved

Optional Equipments



cod. **IA-2**: **DUST EXTRACTOR - TWO CONNECTIONS**
DUST EXTRACTOR kit with two suction mouth: complete of dust filter bag in flexible aluminum pipes and hose clamps. The extractor is mounted inside the base and wired to the electrical panel.TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m3 / h- Max total pressure: 85 mm H2O

Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Seq. 02003 - Rel. 260821
Copyright © Aceti Macchine s.n.c. | All rights reserved