ART.59

Belt grinding machine




Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com

ART 59

LEVIGATRICE A NASTRO PROFESSIONAL
PROFESSIONAL BELT GRINDING MACHINE
BACKSTAND PROFESSIONNELLE
BERUFLICHE BANDSCHLEIFMASCHINE



Volt 400 kW 5.2

hp	Rpm	m/s	E	F	G	G1	dB	kg	A	B	C	D	Ø	ASP.01
7	700 1400	9 18	1100	1700	1100	890	75	500	3100	500	1000	550	250	kW 1.5

Seq. 06003 - Rel. 200622
Copyright © Aceti Macchine s.n.c. | All rights reserved

General technical info

Power supply	400 | 50 | 3	Volt|Hz|Phase
Motor power	5,50 - 3,0 (7,5 - 4,0)	kW (hp)
Motor speed	1400 - 700	rpm
Acoustic emission	75	dB
Overall dimension (Width x Depth x Height)	1700 x 1100 x H. 1100	mm
Weight standard machine	500	kg

• Belt grinder unit

Abrasive belt dimension (wide x length)	500 x 3100	mm
Peripheral speed	18 - 9	m/sec
Dimension of working plane (behind abrasive belt)	550 x 1000	mm
Driving wheel dimension	ø 250	mm
Orientable belt grinding arm	0	°

Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments



Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base
Strong base with anti-vibration rubbers at the base and a useful shelf for tools inside.

Electrical panel
Low voltage electric controls with padlock device integrated in the main electric switch.

Electronic brake card
Emergency stop with electronic motor braking with safety anti-reset function.

Motor
Motor 2 speeds

Seq. 06003 - Rel. 200622
Copyright © Aceti Macchine s.n.c. | All rights reserved

Arm sander
Belt sander in horizontal position.

Rubberized grooved wheel
Rubberized, grooved and balanced drive wheel for better drag of the abrasive belt.

Work surface
Behind the abrasive tape has a durable floor in abutment replaceable steel over time.

Wheel processing
Ability to work in the vicinity of the wheel with a large contact surface.

Abrasive belt
Abrasive belt mounted on the machine ready for use.

Belt grinder cover
Carter sander with predisposition connection system.

Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Seq. 06003 - Rel. 200622
Copyright © Aceti Macchine s.n.c. | All rights reserved