

ART.24

Disc grinding machine



Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com

ART. 24	LEVIGATRICE A DISCO GRINDING DISK-MACHINE LAPIDAIRE TELLERSCHLEIFMASCHINE							
 Volt 400 kW 1,8								kg
hp	Rpm	m/s	dB	E	F	G	G1	kg
2,5	1400 2800	30 60	70	600	800	1300	920	105
				 OPTIONAL				
Ø	M	N	J°	IA-1				
400	450	230	0°÷90°	kW 0,55				

Seq. 01001 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

General technical info

Power supply	400 | 50 | 3	Volt|Hz|Phase
Motor power	2,2 - 1,3 (3,0 - 1,8)	kW (hp)
Motor speed	2800 - 1400	rpm
Acoustic emission	70	dB
Overall dimension (Width x Depth x Height)	800 x 600 x H. 1300	mm
Weight standard machine	105	kg

• Abrasive disc grinder unit

Abrasive disc dimension	ø 400	mm
Peripheral speed	60 - 30	m/sec
Support table dimension	450 x 230	mm
Support table revolution	0 ÷ 90	°

Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments



Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base
Strong base with anti-vibration rubbers at the base and a useful shelf for tools inside.

Electrical panel
Low voltage electric controls with padlock device integrated in the main electric switch.

Electronic brake card
Emergency stop with electronic motor braking with safety anti-reset function.

Motor
Motor 2 speeds

Seq. 01001 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

Support plane
Support plane details inclinable with adjustable height.

Disc
Aluminium disc perfectly balanced.

Abrasive disc
Abrasive disc mounted on the machine ready for use.

Belt grinder cover
Carter sander with predisposition connection system.

Anti-spark repair
Transparent protection arrester with friction joint.

Copyright © Aceti Macchine s.n.c. | All rights reserved

Optional Equipments



cod. **IA-1**: **DUST EXTRACTOR - ONE CONNECTION**
DUST EXTRACTOR kit with one suction mouth: complete of dust filter bag in flexible aluminum pipe and hose clamps. The extractor is mounted inside the base and wired to the electrical panel.TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m3 / h- Max total pressure: 85 mm H2O

Seq. 01001 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Copyright © Aceti Macchine s.n.c. | All rights reserved