ART.26

Disc grinding machine



Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com

ART. 26	LEVIGATRICE A DISCO + PULITRICE GRINDING DISK-MACHINE + POLISHING MAC. LAPIDAIRE + POLISSOIR TELLERSCHLEIF-UND POLIERMASCHINE							
								
Volt 400 kW 1,8			G / E	F		G1	kg	
hp	Rpm	m/s	dB	E	F	G	G1	kg
2,5	1400 2800	18 36	70	600	1000	1300	910	120

					
				NOT INCLUDED	OPTIONAL
Ø	M	N	J°	Ø mm	IA-2
400	450	230	0°÷90°	Ø250xØ25	kW 0,55

Seq. 02001 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

General technical info

Power supply	400 | 50 | 3	Volt|Hz|Phase
Motor power	1,9 - 1,1 (2,5 - 1,5)	kW (hp)
Motor speed	2800 - 1400	rpm
Acoustic emission	70	dB
Overall dimension (Width x Depth x Height)	1000 x 600 x H. 1300	mm
Weight standard machine	120	kg

• Abrasive disc grinder unit

Abrasive disc dimension	ø 400	mm
Peripheral speed	60 - 30	m/sec
Support table dimension	450 x 230	mm
Support table revolution	0 ÷ 90	°

• Polisher - Buffer unit

Brush maximum external size	ø 250	mm
Motor shaft diameter	ø 25	mm
Brush maximum wide size	70	mm
Peripheral speed	36 - 18	m/sec

Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments



Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base
Strong base with anti-vibration rubbers at the base and a useful shelf for tools inside.

Electrical panel
Low voltage electric controls with padlock device integrated in the main electric switch.

Electronic brake card
Emergency stop with electronic motor braking with safety anti-reset function.

Motor
Motor 2 speeds

Seq. 02001 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

Support plane
Support plane details inclinable with adjustable height.

Disc
Aluminium disc perfectly balanced.

Abrasive disc
Abrasive disc mounted on the machine ready for use.

Belt grinder cover
Carter sander with predisposition connection system.

Locking accessories
Locking and reducing steel flange for brush, flap wheel with spacers and clamping nuts.

Polishing cover
Carter adjustable for a comfortable and precise positioning of the operator and with predisposition connection system.

Copyright © Aceti Macchine s.n.c. | All rights reserved

Anti-spark repair
Transparent protection arrester with friction joint.

Seq. 02001 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

Optional Equipments



cod. **IA-2**: **DUST EXTRACTOR - TWO CONNECTIONS**
DUST EXTRACTOR kit with two suction mouth: complete of dust filter bag in flexible aluminum pipes and hose clamps. The extractor is mounted inside the base and wired to the electrical panel.TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m3 / h- Max total pressure: 85 mm H2O

Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Seq. 02001 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved