# ART.27

## Polishing machine



Made in Italy

**Aceti Macchine s.n.c.** | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com

| ART. 27 | PULITRICE DOPPIA<br>DOUBLE POLISHING MACHINE<br>POLISSOIR ( 2 POSTES )<br>DOPPELSCHLEIF-UND POLIERMASCHINE |
|---|---|




Volt 400 kW 1,8

| hp | Rpm | m/s | dB | E | F | G1 | L | kg |
|---|---|---|---|---|---|---|---|---|
| 2,5 | 1400<br>2800 | 18<br>36 | 70 | 600 | 1000 | 910 | 300 | 85 |



NOT INCLUDED



OPTIONAL



OPTIONAL

| Ø mm | INVERTER | IA-2 |
|---|---|---|
| Ø250xØ25 | Rpm 0÷3000 | kW 0,55 |



Seq. 02004 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

# General technical info

| | | |
|---|---|---|
| Power supply | 400 \| 50 \| 3 | Volt\|Hz\|Phase |
| Motor power | 1,9 - 1,1 ( 2,5 - 1,5 ) | kW ( hp ) |
| Motor speed | 2800 - 1400 | rpm |
| Acoustic emission | 70 | dB |
| Overall dimension (Width x Depth x Height) | 1000 x 600 x H. 910 | mm |
| Weight standard machine | 85 | kg |

## • Polisher - Buffer unit

| | | |
|---|---|---|
| Brush maximum external size | ø 250 | mm |
| Motor shaft diameter | ø 25 | mm |
| Brush maximum wide size | 70 | mm |
| Peripheral speed | 36 - 18 | m/sec |
| Operators | 1 | No. |
| Stations | 2 | No. |


Copyright © Aceti Macchine s.n.c. | All rights reserved

# Standard Equipments



**Machine respect CE stamp of compliance**
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.




**Guarantee of European standards**
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

**Base**
Strong base with anti-vibration rubbers at the base and a useful shelf for tools inside.

**Electrical panel**
Low voltage electric controls with padlock device integrated in the main electric switch.

**Electronic brake card**
Emergency stop with electronic motor braking with safety anti-reset function.

**Motor**
Motor 2 speeds



Seq. 02004 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

**Polishing cover**
Carter adjustable for a comfortable and precise positioning of the operator and with predisposition connection system.

**Locking accessories**
Locking and reducing steel flange for brush, flap wheel with spacers and clamping nuts.

**Anti-spark repair**
Transparent protection arrester with friction joint.


Copyright © Aceti Macchine s.n.c. | All rights reserved

# Optional Equipments



cod. **IA-2**: **DUST EXTRACTOR - TWO CONNECTIONS**
DUST EXTRACTOR kit with two suction mouth: complete of dust filter bag in flexible aluminum pipes and hose clamps. The extractor is mounted inside the base and wired to the electrical panel.TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m3 / h- Max total pressure: 85 mm H2O



Seq. 02004 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

# Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.


Copyright © Aceti Macchine s.n.c. | All rights reserved