ART.95

Polishing machine



Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com

ART. 95

PULITRICE SOSPESA PROFESSIONAL
PROFESSIONAL SUSPENDED POLISHING MACHINE
POLISSOIR SUSPENDUE PROFESSIONNEL
BERUFLICHE HÄNGEND POLIERMASCHINE















Volt 400 kW 5.5												
hp	Rpm	m/s	E	F	G1	L	dB	kg	Ø mm	Rpm	INVERTER	ASP.01
7.5	1400 2800	29 58	1450	1050	430÷1500	1000	70	425	Ø400xØ35	700÷1400	Rpm 0÷3000	kW 1.5

Seq. 07004 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

General technical info

Power supply	400 | 50 | 3	Volt|Hz|Phase
Motor power	7,2 - 5,3 (9,8 - 7)	kW (hp)
Motor speed	2800 - 1400	rpm
Acoustic emission	70	dB
Overall dimension (Width x Depth x Height)	1050 x 1450 x H. 430 ÷ 1500	mm
Weight standard machine	425	kg

• Polisher - Buffer unit

Brush maximum external size	ø 400	mm
Motor shaft diameter	ø 35	mm
Brush maximum wide size	75	mm
Peripheral speed	58 - 29	m/sec

Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments



Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Electrical panel
Low voltage electric controls with padlock device integrated in the main electric switch.

Electronic brake card
Emergency stop with electronic motor braking with safety anti-reset function.

Motor
Motor 2 speeds

Polishing cover
Carter adjustable for a comfortable and precise positioning of the operator and with predisposition connection system.

Seq. 07004 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

Locking accessories
Locking and reducing steel flange for brush, flap wheel with spacers and clamping nuts.

Anti-spark repair
Transparent protection arrester with friction joint.

Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Seq. 07004 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved