ART.107

Grinding machine



Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com


ART. 107

SMERIGLIATRICE
GRINDING MACHINE
TOURET A 2 MEULES
SCHEIBENSCHLEIFMASCHINE



Volt 400 kW 1,8





kg

hp	Rpm	m/s	dB	E	F	G	G1	kg
2,5	1400	22	69	610	720	1200	930	130



Ø mm

Ø300x35xØ30



OPTIONAL

IA-2

kW 0,55

Seq. 01300 - Rel. 200721
Copyright © Aceti Macchine s.n.c. | All rights reserved

General technical info

Power supply	400 | 50 | 3	Volt|Hz|Phase
Motor power	1,85 (2,5)	kW (hp)
Motor speed	1400	rpm
Acoustic emission	69	dB
Overall dimension (Width x Depth x Height)	720 x 610 x H. 1200	mm
Weight standard machine	130	kg

• Grinder unit

Grinding wheel maximum external size	ø 300	mm
Motor shaft diameter	ø 30	mm
Grinding wheel maximum wide size	35	mm
Peripheral speed	22	m/sec

Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments







Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base
Strong base with anti-vibration rubbers at the base and a useful shelf for tools inside.

Electrical panel
Low voltage electric controls with padlock device integrated in the main electric switch.

Electronic brake card
Emergency stop with electronic motor braking with safety anti-reset function.

Locking accessories
Locking and reducing steel flange for grinding wheel with spacers and clamping nuts.

Seq. 01300 - Rel. 200721
Copyright © Aceti Macchine s.n.c. | All rights reserved

Support
Plan special adjustable support according to the diameter of the grinding wheel.

Disc grinding wheel
Grinding wheel disc mounted on the machine ready for use.

Grinder cover
Cover with predisposition connection system with predisposition connection system.

Anti-spark repair
Transparent protection arrester with friction joint.

Copyright © Aceti Macchine s.n.c. | All rights reserved

Optional Equipments



cod. **IA-2**: **DUST EXTRACTOR - TWO CONNECTIONS**
DUST EXTRACTOR kit with two suction mouth: complete of dust filter bag in flexible aluminum pipes and hose clamps. The extractor is mounted inside the base and wired to the electrical panel.TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m3 / h- Max total pressure: 85 mm H2O

Seq. 01300 - Rel. 200721
Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Copyright © Aceti Macchine s.n.c. | All rights reserved