

ART.132

Polishing machine



Made in Italy

Aceti Macchine s.n.c. | 24060 Bolgare (Bergamo) Italy - Via ai Dossi, 32 | P.Iva: IT01715640163
Tel. +39 035 843 751 | Fax +39 035 841 624 | info@aceti.com

ART. 132	PULITRICE DA BANCO POLISHING MACHINE FOR DESK POLISSOIR DE BANC POLIERMASCHINE FÜR WERKBANK							
 Volt 400 kW 1,1								
hp	Rpm	m/s	dB	E	F	G	G1	kg
1,5	2800	30	69	590	350	300	175	28
 NOT INCLUDED				OPTIONALS				
				 Volt 230/1F				
Ø mm				INV.MF				BAS.01
Ø200x50xØ20				Rpm 0÷3000				ASP.04

Seq. POL10 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

General technical info

Power supply	400 | 50 | 3	Volt|Hz|Phase
Motor power	1,1 (1,5)	kW (hp)
Motor speed	2800	rpm
Acoustic emission	69	dB
Overall dimension (Width x Depth x Height)	590 x 350 x H. 300	mm
Weight standard machine	28	kg

• Polisher - Buffer unit

Brush maximum external size	ø 200	mm
Motor shaft diameter	ø 20	mm
Brush maximum wide size	40	mm
Peripheral speed of brush	30	m/sec

Copyright © Aceti Macchine s.n.c. | All rights reserved

Standard Equipments



Machine respect CE stamp of compliance
- Machine with CE conformity mark made respecting the requirements of the most recent
  directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and
  exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards
The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base
Stable bench structure with anti-vibration rubbers at the base.

Electrical panel
Electric controls with emergency stop and anti-reset function for accidental starting and electronic overload protection.

Polishing cover
Carter adjustable for a comfortable and precise positioning of the operator and with predisposition connection system.

Locking accessories
Locking and reducing steel flange for brush, flap wheel with spacers and clamping nuts.

Seq. POL10 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

Anti-spark repair
Transparent protection arrester with friction joint.

Copyright © Aceti Macchine s.n.c. | All rights reserved

Optional Equipments



cod. **BAS.02+IA-2**: **MACHINE STAND WITH DUST EXTRACTION TWO CONNECTIONS**
Stand with dust extractor kit with two suction mouth: complete of dust filter bag in flexible aluminum pipe and hose clamps. The extractor is wired to the electrical panel.TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m3 / h- Max total pressure: 85 mm H2O



cod. **M2V-TA**: **TWO SPEEDS MOTOR**
Two speeds three-phase motor Rpm 1400/2800, recommended for use with stainless steel and aluminum.400 volts - 50 Hz - 3 phase



cod. **INV-MF**: **VARIABLE SPEEDS SINGLE PHASE**
Single-phase inverter for electronic regulation of motor revolutions from 300 ÷ 3000 Rpm.The inverter is supplied inside box for the dust protection, which can be controlled with potentiometer.Motor with maximum power 1,1 kW.

Seq. POL10 - Rel. 240621
Copyright © Aceti Macchine s.n.c. | All rights reserved

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.

Copyright © Aceti Macchine s.n.c. | All rights reserved